



Industrie Service

FIRE TEST QUALIFICATION CERTIFICATE

Applus⁺ RTD

NDT & Inspection

Item	Ball Valve
Size	2"
Class	600 lbs
A⁺ RTD ID No.	A ⁺ 53551001
Stem seal material	Expanded Graphite
Body material	316/316L
Seat material	316/316L
Manufactured by	Habonim
In accordance with PO no.	40147774
In accordance with drawing no.	20 47Z-6666MNG/NPT05-FIRETEST

The above valve was tested by Applus RTD Meettechniek at their valve testing facilities in Kapelle, the Netherlands. And the results have been recorded as PASS, having complied with the minimum performance requirements stated in specification:

ANSI/API Standard 607 6th Edition, September 2010
&
ISO 10497:2010, Testing of valves
Fire type-testing requirements

Test date	5 th of October
Other sizes qualified	2 inch and below, 2.5 inch; 3 inch and 4 inch DN 50 and below ,DN65; DN80 and DN100
Other pressure ranges qualified	600 Lbs,800 Lbs and 900 Lbs PN 100 and PN 150

Tested by:



F. Huiszoon (A⁺ RTD)

Date: 05/10/2010

Witnessed by:



P. Deleu (TÜV SÜD)

Date: 05/10/2010

This certificate must be read in conjunction with the full Applus RTD Meettechniek test report number:

053551-R001