



Industrie Service

FIRE TEST QUALIFICATION CERTIFICATE

Applus⁺ RTD

NDT & Inspection

Item	AF47P Dual Safe Valve
Size	2"
Class	600 lbs
A⁺ RTD ID No.	48039002
Body material	SS 316L
Seat material	NRG(carbon filled FTFE)
Manufactured by	HABONIM.
In accordance with PO no.	4013880
In accordance with drawing no.	20-AF47P-4466PG-600-DS05SW

The above valve was tested by Applus RTD Meettechniek at their valve testing facilities in Kapelle, the Netherlands. And the results have been recorded as PASS, having complied with the minimum performance requirements stated in specification:

ANSI/API Standard 607 Fifth Edition, June 2005
&
ISO 10497-5:2004 (Identical), Testing of valves
Fire type-testing requirements

Test date	March 26 th 2010
Other sizes qualified	2" and below, 2 1/2"; 3" and 4" DN 50 and below, DN 65; DN80 and DN100
Other pressure ranges qualified	600 lbs, 800lbs and 900 lbs PN 100 and PN 150

Tested by: 
F. Huiszoon


F. Huiszoon (A⁺ RTD)
Date: 31/03/2010

Witnessed by: 
P. Deleu (TÜV SÜD)
Date: 31/03/2010


This certificate must be read in conjunction with the full Applus RTD Meettechniek test report number:
048039-R002